



Aquafix

Product description

Aquafix is a plasto-elastic, one-component sealant based on copolymers.

Properties

- Crystal clear formulation
- Easy to apply
- Solvent based
- Very good adhesion on many materials
- Can be painted over after curing
- Limited UV-resistant

Applications

- Repair product for leaks in gutters, drainpipes.
- Implementing emergency repairs, even in rain.
- Sealant at cracks and seams.



Technical data

Base	Styrene acrylate
Consistency	Paste
Curing system	Physical drying
Skin formation	ca. 10 minutes
Density	ca. 0.95 g/ml
Maximum allowed joint movement	ca. 10 %
Shrinkage after curing	ca. 20%
Application temperature	+5°C → +30°C
Temperature resistance	-20°C → +90°C

Footnote: Skinning time and curing speed may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Substrates

- Substrate condition
The surface must be rigid, clean, dry or slightly moist, free of dust and grease.
- Substrate types
Aquafix has a good adhesion to following substrates: all usual building substrates. We recommend a preliminary adhesion and compatibility test on every surface.

Application method

- Application method
Apply the product with a manual, pneumatic or accu caulking gun.
- Cleaning method
Clean with White Spirit or Soudal Surface Cleaner immediately after use (before curing).
- Finishing method
With Finishing Solution before skinning.



Aquafix

- Repair method
Repair with the same material.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.
Dangerous. Respect the precautions for use.

Packaging/Logistics

Colour: Please consult the product catalogue, the Soudal website or a Soudal representative.
Packaging: Please consult the product catalogue, the Soudal website or a Soudal representative.
Shelf life: 12 months in unopened packaging in a cool and dry storage place at temperatures between +5°C and +25°C

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.