



Celluplast

Product description

Celluplast is a 1-component, ready for use cellulose finishing putty.

Properties

- Easy to apply
- Fast drying
- Flexible
- Only apply in thin layers
- Lasting adhesion

Applications

- Filling of dents, scratches and cracks on car body, polyester and wood...
- The final finishing layer before painting or spraying.
- Repair of damages on the surface of cars, boats, surf boards, ...
- Finishing layer in case of small bumps and holes in polyester filler.



Technical data

Base	Nitrocellulose
Consistency	Paste
Curing system	Physical drying
Drying time	30 - 60 minutes
Density	ca. 1,51 g/ml
Application temperature	+10°C → +25°C

Footnote: Skinning time and curing speed may vary depending on environmental factors such as temperature, moisture, and type of substrates.

Substrates

- Substrate condition
The surface must be rigid, clean, dry, free of dust and grease.
- Substrate preparation
Remove rust. Rough grinding of smooth surfaces improves the adhesion.
- Substrate types
Celluplast has a good adhesion to following substrates: metals, polyester, wood. We recommend a preliminary adhesion and compatibility test on every surface.

Application method

- Application method
Apply a thin layer of Celluplast with a spatula. Repeat this treatment until the surface is smooth. Allow a layer to dry for at least 30 minutes before applying the next. Sand down after 60 minutes with fine sanding paper while the surface is made wet. Rinse afterwards with water and wipe dry with a soft cloth. The repaired part can now be painted.
- Cleaning method
Clean with acetone.



Celluplast

- Repair method
Repair with the same material.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Consult the packaging label and safety data sheet for more information.
Use only in well-ventilated areas.

Packaging/Logistics

Colour: Please consult the product catalogue, the Soudal website or a Soudal representative.
Packaging: Please consult the product catalogue, the Soudal website or a Soudal representative.
Shelf life: 9 months in unopened packaging in a dry and cool storage at temperatures between +5°C and +25°C.

Remarks

- Not suitable for galvanized surfaces.

This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. It is general in nature and does not constitute any liability. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application. In every case it is recommended to carry out preliminary experiments. The manufacturer reserves the right to modify products without prior notice.