

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Sanitary Sealant Easy

Revision: 11/01/2022

Page 1 from 4

Reference nr DOP: 231856

Unique identification code of the product type:

Soudal Sanitary Sealant Easy

Intended use or uses of the construction product:

**Sealant for facade for interior application.
Sealants used for sanitary applications.**

Construction product in accordance with applicable harmonized specifications:

**EN 15651-1:2012: Type F -INT
EN 15651-3:2012: Type S: CLASS S1**

System or systems of assessment and verification of consistency of performance of the construction product, as set out in Annex V:

**System 3: for essential characteristics
System 3: for reaction to fire**

Name and contact address of the manufacturer as required pursuant to Article 11(5):

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

The notified body:

IFT Rosenheim GmbH, NB 0757 has carried out Determination of the Product Type under system 3.

Declaration of Performance

In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Sanitary Sealant Easy

Revision: 11/01/2022

Page 2 from 4

Declared Performance: EN 15651-1:2012

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class E	EN 15651-1:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 20%	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Durability	Pass	

Conditioning:
Method B

Test substrate:
Aluminium
Mortar

Declared Performance: EN 15651-3:2012

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class E	EN 15651-3:2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 20%	
Adhesion/cohesion at maintained extension after water immersion	NF	
Microbiological growth	0	
Durability	Pass	

Conditioning:
Method B

Test substrate:
Aluminium
Glass

The performance of this product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Declaration of Performance


In accordance with the CPR Regulation (EU) N° 305/2011

Soudal Sanitary Sealant Easy

Revision: 11/01/2022

Page 3 from 4

Signed for on behalf of the manufacturer by



Ing. W. Dierckx

Technical Product Manager
B-2300 Turnhout, Belgium, 11/01/2022

CE marking

In accordance with the CPR Regulation (EU) N° 305/2011

Revision: 11/01/2022

Page 4 from 4



NB 0757

Soudal NV, Everdongenlaan 18-20, 2300 Turnhout, Belgium

22

Reference nr DOP: 231856

EN 15651-1: 2012

EN 15651-3: 2012

Sealant for facade for interior application.

Sealants used for sanitary applications.

Soudal Sanitary Sealant Easy

EN 15651-1:2012: Type F -INT

EN 15651-3:2012: Type S: CLASS S1

Conditioning:

Method B

Substrate:

Aluminium

Mortar

Essential Characteristics	Performance	Harmonized Technical Specification
Reaction to fire	Class E	EN 15651-1: 2012 EN 15651-3: 2012
Release dangerous chemicals	NPD	
Water and air tightness		
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 20%	
Adhesion/cohesion at maintained extension after water immersion	NF	
Elongation at break	≥ 25%	
Microbiological growth	0	
Durability	Pass	